

A premium blended cellulose bonded fiber matrix made from the toughest agricultural fibers, with the added benefit of 10% pre-blended tackifier. Evolution BFM outperforms other products in its class according to third party rainfall erosion control testing, with an effective rate of 99.5 %. The natural fibers break down slowly, protecting the soil for long term erosion protection, lasting over 12 months.



Photos courtesy of Apex Erosion Control (top) and Mark Seeding (bottom)



NaturesOwn
We've Got You Covered

ADVANTAGES

- Fast to load from easy to handle bales
- Mixes easily with water
- Flows smoothly and gives you uniform distribution
- Provides all the benefits of naturally long interwoven fibers while utilizing wood cellulose mulch coverage benefits as well as the binding strength of Triple Tac™ tackifier

APPLICATIONS

- Aerial
- Hydro-Seeding
- Extreme Erosion Control

TYPICAL PROJECTS

- Dust Control
- Highways
- Golf Courses
- Forest Fire Reclamation
- Mine Reclamation

product specifications

Packaging: 50 lb bales

Shipment: 2250 lb pallet

Typical Application Rate:	Hydro-Mulching:	
	Mod. to 3:1	2300 lb/acre
	3:1 to 2:1	3500 lb/acre
	Greater than 2:1	4000 lb/acre

PHYSICAL PROPERTIES

- Water Holding Capacity >1200%
- Moisture Content 12% +/- 3
- Organic Matter >95%
- Ash Content <5%
- pH Range 7.1 +/- 2
- Blended Tackifier 10% + 3%.

Distributed by:



Hamilton Manufacturing, Inc.

901 Russet Street • Twin Falls, ID 83301 USA
Office: (208) 733-9689 • Fax: (208) 733-9447 • Email: info@hmi-mfg.com
Order desk: 800-777-9689 • Web: www.hmi-mfg.com

Printed on recycled stock 

Call us at 800-777-9689 (US Customers) or (208) 733-9689 (International Customers)
Ask about our hydro-seeding equipment and our product guarantee